

HIPRO SERIES TORCHES HI-PRO 180 / 250 / 260 / 400

SALIENT FEATURES

- All types of end connectors available
- Flexible cable assembly for easy access
- Co-axial cable with special rubber sheathing for longer life
- Lightweight torches for maximum comfort and productivity with swivelling handle
- Float type switch assembly for positive contact & longer life
- Ergonomically designed handle
- Optional custom-built torches for specific applications



BRIEF SPECIFICATIONS:

PARAMETERS	TYPES	HI-PRO180E HI-PRO180S	HI-PRO250E HI-PRO250S	HI-PRO260E HI-PRO260S	HI-PRO400E HI-PRO400S
Max.current					
Carrying Capacity @60% Duty Cycle:					
Under CO ₂	Amp	180	250	260	400
Under Argon rich mixture	Amp	150	200	210	320
Cable	Type	Co-axial	Co-axial	Co-axial	Co-axial
Torch Length*	Mtr	3.0	3.0	3.0	3.0
Cooling	Type	Gas cooled	Gas cooled	Gas cooled	Gas cooled
Suitable for wires dia.:					
Steel	mm	0.8	0.8 & 1.2	0.8 & 1.2	0.8,1.2,1.6
Aluminium	mm	-	1.2	1.2	1.2 & 1.6
Torch end connector	Type	Standard AWL / Euro connector			
Product code	(E) END	S15.01.002.0280	S15.01.002.0282	S15.01.002.0284	S15.01.002.0286
	(S) END	S15.01.002.0281	S15.01.002.0283	S15.01.002.0285	S15.01.002.0287

Note:

- E - with Euro Connector
- S - with Standard AWL Connector



WELDERS TO THE NATION SINCE 1951
ADOR WELDING LIMITED
 (Formerly Known as Advani-Oerlikon Ltd.)

www.adorwelding.com

