MIG SERIES TORCHES MTG 250 / 400 / 600



SALIENT FEATURES

- Customized design with insulated torch head for longer and trouble free service life
- New stainless steel wire-spiral eliminates problem of rust build-up and consequent wire feeding problems
- · Plug-in connections for easy interchangeability
- Varieties of nozzle sizes available to suit welding joint configurations
- Special models to fit 'Euro' and other wire-feeders
- Ergonomic handle to reduce operator fatigue
- Improved heavy-duty contact tips for long life and greater operational economy
- · Easy availability of spares

BRIEF SPECIFICATIONS:

TORCHES - MTG SERIES

SPECIFICATION	UNIT	MTG-250 (E)	MTG-250	MTG-400 (E)	MTG-400	MTG-600 (E)	MTG-600
Max. current carrying							
capacity @ 60%							
duty cycle:							
Under CO ₂	Amps	250	250	400	400	500	500
Under Argon	Amps	200	200	300	300	350	350
Length	Mtrs.	3.0	3.0	3.0	3.0	3.0	3.0
Cooling	Туре	Gas	Gas	Gas	Gas	Gas	Gas
Suitable for wires:							
Steel	(Ømm)	0.8, 1.2	0.8, 1.2	0.8, 1.2, 1.6	0.8, 1.2, 1.6	0.8, 1.2, 1.6. 2.0	0.8, 1.2, 1.6. 2.0
Aluminium	(Ømm)	1.2	1.2	1.2, 1.6	1.2, 1.6	1.2, 1.6	1.2, 1.6
Torch end connector	Туре	Euro	Std.	Euro	Std.	Euro	Std.
ORDERING CODE	No.	S15.01.002.0047	S15.01.002.0046	S15.01.002.0052	S15.01.002.0051	\$15.01.002.0083	S15.01.002.0082



WELDERS TO THE NATION SINCE 1951

ADDR WELDING LIMITED

